



## DIMETHYL SILICONES

**Applications: Lubricants, Cooling Fluids, Automotive, Thread lubricant, Foam Control**

<i>Product Name</i>	<i>INCI Name</i>	<i>typical properties:</i>		<i>Benefits</i>
		<i>Specific Gravity</i>	<i>Viscosity</i>	
ICM SF 0.65	Dimethicone	1	0.65	<i>water repellent, heat stable, low surface tension, wide operating temperature range, high compressibility, excellent shear strength</i>
ICM SF 1	Dimethicone	1	1.0	
ICM SF 1.5	Dimethicone	1	1.5	
ICM SF 2	Dimethicone	1	2	
ICM SF 5	Dimethicone	1	5	
ICM SF 10	Dimethicone	1	10	
ICM SF 20	Dimethicone	1	20	
ICM SF 50	Dimethicone	1	50	
ICM SF 100	Dimethicone	1	100	
ICM SF 200	Dimethicone	1	200	
ICM SF 350	Dimethicone	1	350	
ICM SF 500	Dimethicone	1	500	
ICM SF 1000	Dimethicone	1	1,000	
ICM SF 5000	Dimethicone	1	5,000	
ICM SF 10,000	Dimethicone	1	10,000	
ICM SF 12,500	Dimethicone	1	12,500	
ICM SF 30,000	Dimethicone	1	30,000	
ICM SF 60,000	Dimethicone	1	60,000	
ICM SF 100,000	Dimethicone	1	100,000	
ICM SF 300,000	Dimethicone	1	300,000	
ICM SF 600,000	Dimethicone	1	600,000	
ICM SF 1,000,000	Dimethicone	1	1,000,000	

**Shelf Life: 2 years from shipment if stored in unopened original container**