Material Safety Data Sheet			Page 1 of 2
Product Name: DOT 3 BRAKE FLUID			J1703
======================================	 L INFORMATION		=======================================
AJ Chemicals Lubricant	s & Equipment Inc	Emergency Telephone Number	
915 Pleasant Street		(804) 737-8707	
Richmond, VA 23223		Date Prepared	
		January 01, 2007	
CHEMICAL FAMILY: G	lycols, Glycol Ethers, Polyols		
Section 2. HAZARDOU			
Paints, Preservatives, & Solve	ents % TLV(Units)	Alloy And Metallic Coatings	% TLV (Units)
Pigments	N/A	Base Metal	N/A
Catalyst	N/A	Alloys	N/A
Vehicle	N/A	Metallic Coatings	N/A
Solvent	N/A	Filler Metal	N/A
A dditirra	NT/A	Plus Coating or Core Flux	NT/A
Additives Others	N/A N/A	Others	N/A
Outers	14/11		
Hazardous Mixtures of other liquids, solids or gases		TLV(units): Not A	Applicable
Section 3: Physical Data			
Section 3: Physical Data Boiling Point (F):		Specific Gravity(H O=1):	
			.991-1.044 @ 60°F
Boiling Point (F):	Minimum	Specific Gravity(H O=1):	.991-1.044 @ 60°F
Boiling Point (F): Vapor Pressure(mm Hg):	Minimum N/A	Specific Gravity(H O=1): Percent, Volatile By Volume (%):	.991-1.044 @ 60°F
Boiling Point (F): Vapor Pressure(mm Hg): Vapor Density(Air=1): Solubility in Water:	Minimum N/A N/A	Specific Gravity(H O=1): Percent, Volatile By Volume (%): Evaporation Rate: 0.01	.991-1.044 @ 60°F
Boiling Point (F): Vapor Pressure(mm Hg): Vapor Density(Air=1):	Minimum N/A N/A Dispersible Yellow to Amber Fluid with Cha	Specific Gravity(H O=1): Percent, Volatile By Volume (%): Evaporation Rate: 0.01	.991-1.044 @ 60°F 0 @ Room Temperature
Boiling Point (F): Vapor Pressure(mm Hg): Vapor Density(Air=1): Solubility in Water:	Minimum N/A N/A Dispersible Yellow to Amber Fluid with Cha	Specific Gravity(H O=1): Percent, Volatile By Volume (%): Evaporation Rate: 0.01 racteristic Glycol Ether.	.991-1.044 @ 60°F 0 @ Room Temperature
Boiling Point (F): Vapor Pressure(mm Hg): Vapor Density(Air=1): Solubility in Water: Appearance and Odor:	Minimum N/A N/A Dispersible Yellow to Amber Fluid with Cha osion Hazard Data	Specific Gravity(H O=1): Percent, Volatile By Volume (%): Evaporation Rate: 0.01 racteristic Glycol Ether.	.991-1.044 @ 60°F 0 @ Room Temperature
Boiling Point (F): Vapor Pressure(mm Hg): Vapor Density(Air=1): Solubility in Water: Appearance and Odor: ===================================	Minimum N/A N/A Dispersible Yellow to Amber Fluid with Cha cosion Hazard Data Mi	Specific Gravity(H O=1): Percent, Volatile By Volume (%): Evaporation Rate: 0.01 racteristic Glycol Ether.	.991-1.044 @ 60°F 0 @ Room Temperature
Boiling Point (F): Vapor Pressure(mm Hg): Vapor Density(Air=1): Solubility in Water: Appearance and Odor:	Minimum N/A N/A Dispersible Yellow to Amber Fluid with Cha cosion Hazard Data Mi LE	Specific Gravity(H O=1): Percent, Volatile By Volume (%): Evaporation Rate: 0.01 racteristic Glycol Ether. nimum 250°F (COP)	.991-1.044 @ 60°F 0 @ Room Temperature
Boiling Point (F): Vapor Pressure(mm Hg): Vapor Density(Air=1): Solubility in Water: Appearance and Odor:	Minimum N/A N/A Dispersible Yellow to Amber Fluid with Cha cosion Hazard Data Mi LE	Specific Gravity(H O=1): Percent, Volatile By Volume (%): Evaporation Rate: 0.01 racteristic Glycol Ether. nimum 250°F (COP) LL: N/A DEL: N/A	.991-1.044 @ 60°F 0 @ Room Temperature

Material Safety Data Sheet Page 2 of 2 _____ **Product Name: DOT 3 BRAKE FLUID** _____ Section 5. Health Hazard Data **Threshold Limit Value:** None Established **Effects of Overexposure:** Respiratory Irritation, Possible Skin Irritation. **Emergency and First Aid Procedures:** Remove Victim to Fresh Air, Wash Off With Soap and Water. Section 6. Reactivity Data -----**Stability:** Stable **Conditions to Avoid:** None **Incompatibility(Materials to Avoid):** Strong Oxidizers **Hazardous Decomposition Products:** None **Hazardous Polymerization:** Will Not Occur. (Conditions to Avoid) None Section 7. Spill or Leak Procedures Steps To Be Taken In Case Material Is Released Or Spilled: Gather Small spills with Oil or Grease Absorbent, Large Spills by vacuum into D.O.T. approved Containers. Waste Handling And Disposal Method: Removal by Authorized Legal Waste Disposal Agency. **Special Protection Information** Section 8. Adequate Ventilation **Respiratory Protection(specify type): Ventilation:** Not Applicable **Protective Gloves:** Rubber **Eye Protection:** Safety Goggles **Other Personal Protective Equipment**: Not Applicable.

Keep Away From Open Flame

None

Section 9. Special Precautions

Other Precautions:

Precautions to Be taken in handling and storing: